



16645 Heimbach Road  
 Three Rivers, MI 49093  
 Phone 269-279-5123  
 Fax 269-279-6337  
[www.wfwells.com](http://www.wfwells.com)

2013



**W. F. WELLS MODEL B-25-2A3 CNC**

**Specifications**

Capacity..... 25" High x 40" Wide, 25½" Diameter Round  
 Weight Capacity..... 14,000 lbs  
 Blade Speed ..... 60-500 SFPM  
 Blade Size ..... 1½" X .050" X 26'-6"  
 Blade Guide..... Spring Tensioned Carbide Blocks with Idle Roller Backup  
 Blade Tension..... Hydraulic  
 Bandwheel Size ..... 26"  
 Vice ..... Hydraulic  
 Blade Drive ..... 10 HP, AC Vector Drive  
 Sawing Force..... 0-1,000 lbs  
 Coolant Capacity ..... 15 Gallons  
 Hydraulic Capacity ..... 20 Gallons  
 Hydraulic Drive ..... 5 HP Motor  
 Work Height..... 35"  
 Outfeed Table..... 12" X 41"  
 Vise Jaw Height..... 17"  
 Barfeed Projection ..... 0 - 36" CNC Controlled  
 Projection Accuracy ..... +/- .002  
 Shuttle Indexes ..... Unlimited  
 Remnant End..... 14"  
 Electrics ..... Wired to NFPA 79 Machine Tool Standards  
 Hydraulic Positioned Guide Arm, Powered Blade Brush, Blade Break/Stall Switch  
 CNC Programmable Controller with Color Touch Screen  
 500+ Job Selection  
 Automatic Kerf Compensation  
 Shipping Weight..... 11,000 Shipping Dimensions..... 170"L x 102"W x 105"H

**Voltage**  
 208-60-3  
 230-60-3  
 460-60-3  
 575-60-3

**OPTIONAL FACTORY INSTALLED ACCESSORIES**

**Description**

Discharge Worktable 40" Wide X 56" Long  
 Hydraulic Chip Conveyor  
 Hydraulic Holddown, Saw Vise  
 Hydraulic Holddown, Barfeed Vise  
 Outboard Vise with Hydraulic Holddown  
 Outboard Vise  
 Non-Powered Conveyor 40" X 5'  
 Non-Powered Conveyor 40" X 10'  
 High Speed Drive & Guides (1¼" Blade) 500-3000 SFPM

**Consult Factory For Additional Accessories**

\*Prices and specifications subject to change without notice

