



16645 Heimbach Road
 Three Rivers, MI 49093
 Phone: 269-279-5123
 Fax: 269-279-6337
www.wfwells.com

2013



W. F. WELLS MODEL B-25-3A3 CNC

Specifications

Capacity..... 25" High x 40" Wide, 25.5" Round
 Weight Capacity..... 14,000 lbs
 Blade Speed 60-500 SFPM
 Blade Size 2" X .063" X 26'-6", 2⁵/₈ optional
 Blade Guide Spring Tensioned Carbide Blocks with Idle Roller Back-up
 Blade Tension..... Hydraulic
 Bandwheel Size 26"
 Vise Hydraulic
 Blade Drive 15 HP, AC Vector Drive
 Sawing Force..... 0-1,000 lbs
 Coolant Capacity 15 Gallons
 Hydraulic Capacity 20 Gallons
 Hydraulic Drive 5 HP Motor
 Work Height..... 35"
 Outfeed Table..... 12" X 41"
 Vise Jaw Height 17"
 Barfeed Projection 0 - 36" CNC Controlled
 Projection Accuracy +/- .002"
 Shuttle Indexes Unlimited
 Remnant End..... 14"
 Electrics Wired to NFPA 79 Machine Tool Standards
 Hydraulic Positioned Guide Arm, Powered Blade Brush, Blade Break/Stall Switch
 CNC Programmable Controlled with Color Touch Screen
 500+ Job Selection
 Automatic Kerf Compensation
 Shipping Weight.....11,400 Shipping Dimensions.....170"L x 102"W x 105"H

OPTIONAL FACTORY INSTALLED ACCESSORIES

Description

Discharge Worktable 40" Wide x 56" Long
 Hydraulic Chip Conveyor
 Holddown, Saw Vise
 Hydraulic Holddown, Barfeed Vise
 Outboard Vise with Hydraulic Holddown
 Outboard Vise
 Non-Powered Conveyor 40" x 5'
 Non-Powered Conveyor 40" x 10'
 High Speed Drive & Guides (1½" Blade) 500-3000 SFPM

Consult Factory for Additional Accessories

*Prices and specifications subject to change without notice

