



16645 Heimbach Road  
 Three Rivers, MI 49093  
 Phone 269-279-5123  
 Fax 269-279-6337  
[www.wfwells.com](http://www.wfwells.com)

2013

**W. F. WELLS MODEL B-25-3C (6° Cant)**

**Specifications**

Capacity .....	Rectangular at 90°	22" High X 40" Wide (25" Round, 24" Square)
	Rectangular at 45°	22" High X 24" Wide
Weight Capacity .....	15,000 lbs	
Blade Speed .....	60-500 SFPM	
Blade Size .....	2" X .063" X 26'-6"	
Blade Guide .....	Spring Tensioned Carbide Blocks with Idle Roller Backup	
Blade Tension .....	Hydraulic	
Bandwheel Size .....	26"	
Vise .....	Hydraulic	<b>Voltage</b> 208-60-3
Blade Drive .....	15 HP, AC Vector Drive	230-60-3
Sawing Force .....	0-1,000 lbs	460-60-3
Coolant Capacity .....	15 Gallons	575-60-3
Hydraulic Capacity .....	20 Gallons	
Hydraulic Drive .....	5 HP Motor	
Work Height .....	34"	
Outfeed Table .....	24" X 40"	
Vise Jaw Height .....	17"	
Hydraulic Positioned Guide Arm		
Hydraulic Powered Blade Brush		
Blade Tension Indicator		
Blade Break/Stall Switch		
Electronic Door Interlocks		
Shipping Weight .....	7,500 lbs	
Electrics .....	Wired to NFPA 79 Machine Tool Standards	
Machine Dimensions .....	170" Length x 55" Width x 105" Height	

**OPTIONAL FACTORY INSTALLED ACCESSORIES**

**Description**

- Discharge Worktable, 40" Wide X 56" Long
- Hydraulic Chip Conveyor, Auger Style
- Hydraulic Holddown, Saw Vise
- Outboard Vise with Hydraulic Holddown
- Outboard Vise
- Laser Shadow Line
- Hydraulic Powered Conveyor 40" X 10'
- Non-Powered Conveyor 40" X 5'
- Non-Powered Conveyor 40" X 10'
- High Speed Drive & Guides (1½" Blade) 500-3000 SFPM

For B-25-3C with Automatic Barfeed see B-25-3CA3 CNC

**Consult Factory For Additional Accessories**

\*Prices and specifications subject to change without notice

**MADE IN USA**