



16645 Heimbach Road
 Three Rivers, MI 49093
 Phone 269-279-5123
 Fax 269-279-6337
www.wfwells.com

2013

W.F. WELLS MODEL F-16-2

Specifications

Capacity.....	Rectangular at 90° 16" High x 20" Wide, Round at 90° 16" Diameter	
	Rectangular at 45° 16" High X 9" Wide, Round at 45° 9" Diameter	
Weight Capacity.....	5,000 lbs	
Blade Speed	60-425 SFPM	
Blade Size	1¼" X .042" X 15'	
Blade Guide.....	Rollers and Carbide Side Blocks	
Blade Tension.....	Hydraulic	
Bandwheel Size	20"	<u>Voltage</u>
Vise	Full Stroke Hydraulic, 8-1/2"	208-60-3
Blade Drive	7½ HP, AC Vector Drive	230-60-3
Sawing Force.....	0-750 lbs	460-60-3
Coolant Capacity	15 Gallons	575-60-3 (5 HP)
Hydraulic Capacity	20 Gallons	
Hydraulic Drive	2 HP Motor	
Work Height.....	26"	
Shipping Weight.....	2,450 lbs	
Electrics	Wired to NFPA 79 Machine Tool Standards	
Machine Dimensions.....	97" Length x 49" Width x 83" Height	

OPTIONAL FACTORY INSTALLED ACCESSORIES

Description

Automatic Length Stop Assembly
 Discharge Worktable, 20" W x 48" L with Stock Stop
 Work Light, Wired In
 Blade Break/Stall Switch
 Hydraulic Chip Conveyor
 Hydraulic Holddown, Saw Vise
 Hydraulic Swivel Base with Miter Vise (See M-16-2)
 Hydraulic Powered Conveyor 21" X 10'
 High Speed Drive & Guides (1" Blade) 400-3000 SFPM
 Hour Meter
 Free Standing Roller Stock Conveyors, 6" Centers:
 18" X 5' X 2,500 lbs Cap. Distributed Weight
 18" X 10' X 5,000 lbs Cap. Distributed Weight
 21" X 5' X 5,000 lbs Cap. Distributed Weight
 21" X 10' X 10,000 lbs Cap. Distributed Weight

Consult Factory For Additional Accessories

*Prices and specifications subject to change without notice

Distributed By:



**Tool
Technology
Distributors, Inc.**

P: 510-656-8220
 P: 800-335-8437
 F: 510-656-2458
 E: info@tooltechnology.com
 W: www.tooltechnology.com

MADE IN USA