



16645 Heimbach Road
 Three Rivers, MI 49093
 Phone 269-279-5123
 Fax 269-279-6337
www.wfwells.com



W. F. WELLS MODEL S-40-3A3 CNC

Specifications

Capacity.....	40" High x 40" Wide	
Weight Capacity.....	14,000 lbs	
Blade Speed	60 - 500 SFPM	
Blade Size	2" X .063" X 29'	
Blade Guide.....	Spring Tensioned Carbide Blocks with Idle Roller Backup	
Blade Tension.....	Hydraulic	
Bandwheel Size	42"	<u>Voltage</u>
Vise	Hydraulic	208-60-3
Blade Drive	15 HP, AC Vector Drive	230-60-3
Sawing Force.....	0-1000 lbs	460-60-3
Coolant Capacity	15 Gallons	575-60-3
Hydraulic Capacity	20 Gallons	
Hydraulic Drive	5 HP Motor	
Work Height.....	34"	
Outfeed Table	12" X 41"	
Vise Jaw Height	24"	
Barfeed Projection	0-36" CNC Controlled	
Projection Accuracy	+/- .002"	
Shuttle Indexes	Unlimited	
Remnant End.....	14"	
Shipping Weight.....	12,200 lbs	
Electrics	Wired to NFPA 79 Machine Tool Standards	
Hydraulic Positioned Guide Arm, Powered Blade Brush, Blade Break/Stall Switch		
CNC Programmable Controlled with Color Touch Screen		
500+ Job Selection		
Automatic Kerf Compensation		
Shipping Weight.....	12,200	Shipping Dimensions.....175'L x 102"W x 135"H

OPTIONAL FACTORY INSTALLED ACCESSORIES

Description

Discharge Worktable 40" Wide X 56" Long
 Hydraulic Chip Conveyor
 Hydraulic Holddown, Saw Vise
 Hydraulic Holddown, Barfeed Vise
 Outboard Vise with Hydraulic Holddown
 Outboard Vise
 Non-Powered Conveyor 40" X 5'
 Non-Powered Conveyor 40" X 10'

Consult Factory For Additional Accessories

*Prices and specifications subject to change without notice

