



16645 Heimbach Road  
 Three Rivers, MI 49093  
 Phone 269-279-5123  
 Fax 269-279-6337  
 www.wfwells.com

J2008



**W. F. WELLS MODEL X-6025-4**

**Specifications**

Capacity .....	Rectangular at 90° 60" High X 60" Wide		
Length of Cut.....	25"		
Weight Capacity .....	20,000 lbs		
Blade Speed.....	75-500 SFPM		
Blade Size .....	2" X .063" X 26'-6"		
Blade Guide .....	Carbide Blocks with Roller Backup		
Blade Tension .....	Hydraulic		
Bandwheel Size .....	26"	<b><u>Voltage</u></b>	<b><u>Order Number</u></b>
Vise .....	None	208-60-3	0011
Blade Drive.....	15 HP, 3ph, AC Vector Drive	230-60-3	0011
Positive Sawing Force.....	0-1000 lbs	460-60-3	0011
Coolant Capacity.....	20 Gallons	575-60-3	0011
Hydraulic Capacity .....	20 Gallons		
Hydraulic Drive.....	5 HP Motor		
Work Height .....	16"		
Blade Tension Indicator			
Electronic Door Interlocks			
Free Standing Operator Control Station			
LED Positive Feed Readout			
Work Support .....	62" Wide x 36" Deep		
Shipping Weight.....	8,000 lbs		
Electrics .....	Wired to NFPA 79 Machine Tool Standards.		
Dimensions .....	13'6" Wide x 66" Deep x 112" High		

**Positive Frame Feed** allows the head to descend at a fixed IPM rate for optimum cutting in those high production applications where similar types of material are cut repetitively. Hydraulic down pressure moves the blade through the hardest material at a constant rate.

**OPTIONAL FACTORY INSTALLED ACCESSORIES**

<b><u>Description</u></b>	<b><u>Order Number</u></b>
High Speed Drive & Guides 330-2,000 SFPM (1½")	0056297
Dust Collection Outlet Drive On Door	0520603
2⅝" Blade Option	
50 Cycle Voltage	0056295

**Consult Factory For Additional Accessories**

